

## PRODUCT INFORMATION



QUIKRETE® is a registered trademark of QUIKRETE® International, Inc.  
U.S. Trad. Off. Reg. Nos. 391,990; 767,396; 1,042,903  
© 2005 Quikrete International, Inc., Atlanta, GA 30305



**PRODUCT: 02-51795**

### DESCRIPTION:

QUIKRETE® Anti-Skid Floor Texture Additive

### FEATURES:

Anti-Skid Floor Texture Additive, when mixed with sealers, floor paint, or epoxies enhances traction on concrete, wood, metal or fiberglass surfaces. Anti-Skid Additive will not change the color, properties or performance of the coating. Particularly valuable in areas used by children and the elderly, or areas subject to snow, rain or other wet conditions.

### WHERE TO USE:

Use on stairs, ramps, garages, pool areas, porches, basements, walkways, patios and decks.

### DIRECTIONS:

Mix 1.5 oz. (1/2 of this pouch) of Anti-Skid Floor Texture Additive per gallon of paint or stain. For added anti-skid properties, use 3 oz. (entire pouch) per gallon of paint or stain. Add slowly while stirring and mix thoroughly before and during use.

### PACKAGING:

3 oz.—6 Pack

### Product Information Hotline:

**1-800-458-0047**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. We assume no obligation or liability for use of this information. UNLESS WE AGREE OTHERWISE IN WRITING, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIM ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. WE WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.

### CAUTION:

MAY CAUSE EYE, SKIN, NOSE AND THROAT IRRITATION. **Use only with adequate ventilation.** Avoid breathing powder by wearing an appropriate particulate respirator. Avoid contact with eyes and skin. Wear protective glasses, gloves and other appropriate clothing. Loose, dry material may create a slip hazard. Sweep up and place in appropriate disposal container. Close container after use. Wash thoroughly after handling.

### FIRST AID:

**EYE CONTACT:** Flush immediately with water for at least 15 minutes. **Get medical attention.**  
**SKIN CONTACT:** Wash thoroughly with soap and water. If irritation persists, **get medical attention.**  
**IF SWALLOWED:** Induce vomiting. **Get medical attention.**  
**IF INHALED:** Remove to fresh air. If breathing difficulty continues, **get medical attention.**

**DO NOT TAKE INTERNALLY.**

**KEEP OUT OF REACH OF CHILDREN.**

**For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:**

**1-888-345-5732**

**02-51795 QUIKRETE Anti-Skid Floor Texture Additive**