

PRODUCT INFORMATION



QUIKRETE® is a registered trademark of QUIKRETE® International, Inc.
U.S. Trad. Off. Reg. Nos. 391,990; 767,396; 1,042,903
© 2005 Quikrete International, Inc., Atlanta, GA 30305



PRODUCT: 50079

DESCRIPTION:

QUIKRETE® Etching Stain High Gloss Sealer

FEATURES:

This sealer is designed to be used as a top coat over QUIKRETE Etching Stain. Use it to waterproof and enhance the Etching Stain finish with a glossy, wet-look sheen. This sealer is fortified with new, heavy-duty resin technology to protect your exterior surfaces against the sun's UV rays and damaging weather. Resists gasoline, deicing salts and household chemicals.

SURFACE PREPARATION:

Note: This product will seal out water and other stains, but will not correct moisture problems coming from within the surface. Test for moisture by taping aluminum foil or plastic wrap to the surface for 24-48 hours. If the surface is damp when the aluminum or plastic is removed, moisture migration is present. The source of the moisture must be corrected before using this product or it may turn white upon drying.

General:

All surfaces must be clean, dry and free of all loose, peeling paint or contaminants. Wash all surfaces, rinse well and thoroughly dry overnight before applying.

Bare Concrete: Allow 60 days minimum for new concrete to cure before sealing.

Previously Sealed Surfaces:

Clean with an all purpose cleaner (TSP or substitute) followed by a clean water rinse and dry thoroughly. Previously sealed surfaces must be porous and able to accept additional sealer.

Test Surface Porosity Before Sealing:

Avoid using this product on non-porous, sealed surfaces. To test, place a few drops of water on surface. If water sinks in, the surface is porous enough to use this finish. If water remains on the surface, do not use.

TYPICAL PRODUCT PROPERTIES: (50079)

VEHICLE TYPE: Acrylic-Alkyd Resin

SOLIDS: 32% WT. 26% VOL.

VOC: 600 g/L max

WT/GAL: 7.7 lbs.

VISCOSITY: 12-14 sec #4 Ford Cup

FLASHPOINT: 62 F

60° GLOSS: 80+ units, sealed surface

COVERAGE/THINNING:

Covers approximately 200-400 sq. ft. (18.37 m²) per gallon depending upon surface porosity. Do not thin.

FILM THICKNESS:

4-8 Wet Mills 1-2 Dry Mills

DRY TIMES:

Apply only when surface and air temperatures are 50-90°F (10-32°C). Do not apply to wet or damp surfaces, or areas prone to ponding water. Dries to the touch in 2 hours. Recoat after 2 hours. Wait 24 hours for light use.

02-50079 QUIKRETE Etching Stain High Gloss Sealer

APPLICATION:

Apply with a premium quality roller, brush or lambs wool applicator. If the first coat sinks in rapidly, apply a second coat after 2 hours. Allow to soak for 10-15 minutes - or until pores are completely sealed. Wipe off surplus from the surface before the sealer dries.

CLEAN UP:

Clean up with xylene.

PACKAGING:

Gallons 6 Pack

STORAGE AND DISPOSAL:

Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations. **Danger:** Rags, steel wool, sanding dust or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool, sanding dust or waste in a sealed, water-filled metal container.

Product Information Hotline:

1-800-458-0047

DO NOT TAKE INTERNALLY.**KEEP OUT OF REACH OF CHILDREN.**

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

This product contains less than
600 g/L VOC (5.0 lb./gal VOS)

TYPICAL ANALYSIS (50079)

C.A.S. NO.	INGREDIENTS
160870-25-7	Acrylic Alkyd Resin
64742-95-6	Aromatic Naphtha, Light
95-63-6	1,2,4-Trimethylbenzene
67-64-1	Dimethyl Ketone
1330-20-7	Xylene
64742-47-8	Mineral Spirits
100-41-4	Ethylbenzene

CAUTIONS:**CONTAINS ORGANIC SOLVENT**

Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. May be harmful if absorbed through skin. Harmful if swallowed. Keep away from heat, sparks and flame. Vapors may cause flash fire. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent buildup of vapors by opening doors and windows to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, or if air monitoring demonstrates vapor/mist levels above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. Close container after use. **Warning:** This product contains chemicals known to the State of California to cause cancer.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.**

SKIN CONTACT: Wash thoroughly with soap and water.

IF INHALED: If you experience difficulty in breathing, leave the area to obtain fresh air. If breathing difficulty continues, **get medical attention immediately.**

IF SWALLOWED: Do not induce vomiting. **Get medical attention immediately.**

Delayed effect from long-term exposure: Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. We assume no obligation or liability for use of this information. **UNLESS WE AGREE OTHERWISE IN WRITING, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIM ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. WE WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.